




输入 / 输出电缆







用于动态传感器、电源和仪器

如欲订购，请访问 cn.omega.com/acc-cables，了解价格和详情

电源/加速计接口电缆

型号	连接器 A	电缆	连接器 B
ACC-CB1-6 ACC-CB1-15	 BNC母连接器	1.83 m (6') 4.58 m (15') 4.8 mm (0.190") 直径同轴电缆	 BNC公连接器
ACC-CB2-10	 10-32公插头	3.05 m (10') 2.0 mm (0.080") 直径同轴电缆	 BNC公连接器
ACC-CB3-6 ACC-CB3-15	 4针1/4-28公插头	1.83 m (6') 4.58 m (15') 4.8 mm (0.190") 直径同轴电缆 用于三轴加速计	 4-针 1/4-28 母插头

电源/仪器接口电缆

型号	连接器 A	电缆	连接器 B
ACC-CB4-6 ACC-CB4-15	 BNC母连接器	1.83 m (6') 4.58 m (15') 4.8 mm (0.190") 直径同轴电缆	 BNC母连接器
ACC-CB5-2	 BNC母连接器	0.61 m (2') 4.8 mm (0.190") 直径同轴电缆	 香蕉插头
ACC-CB6	 BNC母连接器	0.18 m (7") 20 AWG 铜线	 尾纤

典型系统框图

